



• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM**®

**Imagine, spray, create!**

## PRODUCT DATA

### **CLEAR POLYURETHANE FINISH - USE ONLY AS DIRECTED.**

A quick drying, ultra-tough clear finish for use on wood, metal or painted surfaces. Seals, protects and enhances. Non-yellowing formulation.

**Preparation:** Ensure surfaces to be painted are free from loose paint, rust, wax oil and grease. Previously painted surfaces should be abraded to provide a key. Cover surrounding areas to protect from spray mist.

**Application:** Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

**Cleaning:** Wipe wet paint from tip before storing, if the valve clogs during use, remove and rinse with white spirit.

**Drying and recoating:** Touch Dry in 2 hours. Hard dry in 24 hours.

**Coverage:** The can covers approximately 1.5m<sup>2</sup> per coat dependant upon surface profile/porosity.

**Limitations:** Not for use on vinyl or linoleum, may have a darkening effect on light coloured surfaces. Apply only when temperature is between 10-32°C and relative humidity below 85%.

Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. For further information please contact our technical services department on 01902 712286.



Rustoleum Aerosols, Carver Building, Littles Lane, Wolverhampton WV1 1JY  
Tel: 01902 712286 Email: [sales@rustoleumaerosols.co.uk](mailto:sales@rustoleumaerosols.co.uk)  
Fax: 01902 426574 Web: [www.rustoleumaerosols.co.uk](http://www.rustoleumaerosols.co.uk)