



• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

Imagine, spray, create!

PRODUCT DATA

FROSTED GLASS - USE ONLY AS DIRECTED.

Create a translucent frosted glass effect on transparent surfaces including glass doors, windows, skylights and greenhouses. For a decorative effect, use with stencils to create a beautiful etched glass look on mirrors, glass accessories and more.

Preparation: Ensure surfaces to be painted are free from any loose paint, rust, wax, oil and grease. Cover surrounding areas to protect spray mist.

Application: Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

Cleaning: Wipe wet paint from tip before storing, if the valve clogs during use, remove and rinse with white spirit.

Drying and recoating: Touch Dry in 10 minutes. Recoat any time after Touch Dry.

Coverage: The can covers approximately 1.5m² per coat dependant upon surface profile/porosity.

Limitations: Frosted surfaces may be cleaned with a soft cloth or be hand washed. Do not place in a dishwasher. To remove the frosted finish use acetone or lacquer thinner. Apply only when temperature is between 10-32°C and relative humidity below 85%.

Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. For further information please contact our technical services department on 01902 712286.



Rustoleum Aerosols, Carver Building, Littles Lane, Wolverhampton WV1 1JY
Tel: 01902 712286 Email: sales@rustoleumaerosols.co.uk
Fax: 01902 426574 Web: www.rustoleumaerosols.co.uk