

## PRODUCT DATA

## 1616 - X1 CERAMIC ANTI SEIZE SPRAY

### DESCRIPTION

1616 X1 eXcellent Anti Seize spray is a non-metallic ceramic base grease, capable of withstanding extreme pressures and temperatures. The ceramic technology leaves an inert barrier of microscopic platelets which will help prevent seizure long after greases fail due to high temperature. It provides with an ultra thin film, giving lasting lubrication and protection.

### MAIN PROPERTIES

Good penetrating and lubricating properties - stops squeaking - penetrating properties - water repellent - corrosion preventive - suitable for vertical surfaces, will not run - white colour gives visual confirmation of lubrication - non silicon, bodyshop safe - H1 compliant for incidental food contact - Non metal and non conductive - Insulates, prevents seizure between dissimilar metals - Non silicon.

### RECOMMENDED USES

Lubricating bearings, gears, cables and chains etc. Protection of metal surfaces against rust. Lubricating locks, hinges, and other moving parts. Ideal for tracks and slide conveyors. Water resistant, can be used on water pumps etc.

### TECHNICAL DATA

Appearance:                      Transparent  
 Colour:                            White  
 Operating temperature:    -30°C to 1100°C.

### SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

### DIRECTION FOR USE

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

### APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.  
 Braak 1, 4704 RJ  
 P.O. Box 138, 4700 AC  
 Roosendaal, The Netherlands  
 T +31 (0)165 593 636  
 F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)  
[www.x1techsprays.com](http://www.x1techsprays.com)

N.V. Martin Mathys S.A.  
 Kolenbergstraat 23  
 3545 Zelem  
 Halen, Belgium  
 T +32 (0)13 460 200  
 F +32 (0)13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)  
[www.x1techsprays.com](http://www.x1techsprays.com)

Rust-Oleum France S.A.S  
 11, Rue Jules Verne, B.P. 60039  
 95322 St-Leu-la-Forêt Cedex  
 France  
 T +33 (0)1 30 40 00 44  
 F +33 (0)1 30 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)  
[www.x1techsprays.com](http://www.x1techsprays.com)

Rust-Oleum UK Ltd.  
 Rotterdam House  
 116 Quayside  
 Newcastle, NE1 3DY  
 United Kingdom  
 T +44 (0)2476 717 329  
 F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)  
[www.x1techsprays.com](http://www.x1techsprays.com)